

Maximum Performance



DC 4

FEATURES AND BENEFITS

- New attractive design
- New dimensions (more compact)
- New control (6 automatic programs and time drying)
- Increased capacity up to 6 kg
- Increased heat power
- Better airflow allowing shorter drying times
- Flexible construction allows hanging bars to slide easily forward for easy access to garments or down for more space
- Easy to install; the evacuating channel is connected to the ventilation system and the humid air is transported out of the room
- All electrical components are placed on the top which makes it easy to maintain
- Pull-out hanging system
- 3 temperatures: high, normal, low
- Energy efficient
- Overheat protection
- IP 24 classification
- CE-approved

ТҮРЕ		DC 4
Loading capacity	kg/lb	up to 6 kg / 13
Drying capacity	g/min*	25
Hanging length	m	16/52,5
Heating effect	kW	2
Total effect	kW	2,038
Energy consumption economy / kg	kWh	0.1
Energy consumption express / kg	kWh	0.64
ELECTRICAL CONNECTIONS		
Electrical connection (standard)		1N, 230V, 50/60Hz
Total effect	kW	2,038
Heating elements	kW	2,0
AIR CONNECTIONS		
Outlet exhaust	ø mm	100
Outlet airflow	m³/h	95
Pressure drop	max Pa	60
Dewatering capacity	g/min	25*
SOUND LEVEL		
Airborne sound level	dB(A)	55
DIMENSIONS		
HxWxD	mm	1939x595x619
SHIPPING DATA		
Net	kg	61
Gross (crate)	kg	65
Shipping volume	m³	0.2
* Valid for textile spun at high speed.		

