

ELECTRONIC DISHWASHERS



BE 50 VE



HIGH TECHNOLOGY AND INNOVATION WITH THE SAME STRENGTH AND SIMPLICITY AS ALWAYS




- Frame and body in S/S AISI 304
- LED display with user-friendly symbols
- Stainless steel rotating washing and rinsing arms
- Double skinned door
- 8-key control board for easier operation
- 4 washing cycles with programmable times and temperatures
- Washing options: cold water rinse, sanitization, ECO function
- Operational information: tank signalling (empty, full, filling), boiler and tank temperature, selected program, operational program status
- Tank and boiler heating elements in Incoloy 800
- Boiler holding device

BA TECHNOLOGY


Anti-reflux device with atmospheric boiler to grant consistent water pressure values and water temperature during the rinsing phase (optional)

NEW ELECTRONIC CONTROL BOARD




LED Display

Display of operational times and status with high-luminosity and user-friendly symbols




Machine start/switch-off

Quick starting of the machine in maximum 15 minutes time




Special washing options

4 washing options: standard, cold rinse, sanitizing and ECO




Cycle start

4 washing cycles with programmable temperature, wash time and rinse time




Machine configurations

For the configuration of temperatures, cycles duration, times, rinse-aid detergent, boiler holding and fan duration




Key selections

Menu scroll keys and simple, practical functions




Water drainage

Possibility of water drainage at the end of the cycle (optional)



Machine information

Display of the latest temperatures (HACCP), alarms, estimated water consumption and correct operation



		BE 50 VE
Net/gross weight	kg	60/65
Basket sizes	mm	500 x 500
Cycle lengths	sec	60/120/180 + 10'
Production (P/h)	n°	1320/660/440
Basket capacity Ø24 cm dish	n°	16
Std input voltage (60Hz optional)	V	230~50Hz
Which may be transformed into	V	230~50Hz
Max absorbed power	kW	3.6
Power of wash pump	kW	0.59
Power of boiler/tank heating elements	kW	3 / 2
Capacity of boiler/tank	lt	4,5 / 27
Rinse water consumption (2 bar)	lt	3
Water feed	°C	55...60
Standard supplied coated baskets	n°	2
Detergent pump		●
Rinse aid pump		●
Drain pump		●
Rinsing pressure booster pump		●
Integrated water softener		●

● On request ● Equipment

ELFRAMO SPA

Headquarter - 24127 Bergamo - via A. Verga, 24 /26 /28 Italy • Secondary offices - 24127 Bergamo - via A. Cavalli, 40 Italy
Tel. 035. 4548111 - Fax 035. 4548150 • elframo@elframo.it - www.elframo.com